

HIGH BLOCK C

TDS01 Rev6 01/08/18

DESCRIPTION

Westox Highblock C is a solvent primer based on thermoplastic resins.

USES

A highly adhesive penetrating primer which “locks” into substrate to provide a mechanically stable surface for following surface coatings. It can be used on masonry, fibre cement sheets and all cementitious surfaces and over sound acrylic coatings.

PREPARATION

Drying time touch dry in 20 minutes @ 20°C.

Drying times will be longer on cold or humid days.

Coverage depending on surface 8 – 10m² per Litre.

APPLICATION

The surface to be treated should be clean and sound, free from oil, grease, flaking paint, laitance and material deleterious to the adhesion of the coating system.

Repair unsound substrate.

Surface should not be too smooth.

Apply by brush, roller or airless spray.

Apply small test area if covering an existing coating.

If bubbling occurs this usually indicates that existing coating is unsound and should be removed.

Do not thin out material.

Once High Block C is touch dry, top coat can be applied.

CLEAN UP

Wash all equipment with xylene after use.

PACKAGING

4 Litre.

20 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.

Material is flammable.

DO NOT ALLOW NAKED FLAME NEAR OPEN CONTAINERS.



Westgate Pty Ltd
16 Frost Road, Campbelltown NSW 2560
Ph: 61 2 46285010 Fax: 61 2 46285020
Email: info@westox.com Website: www.westox.com