

SAME DAY SEALER

TDS28 Rev4 01/08/18

Concrete Sealer

DESCRIPTION

Westox Same Day Sealer is specifically formulated for a single pack, clear thermoplastic acrylic co-polymer solution for the sealing of cementitious coatings.

USES

A penetrating sealer designed to provide colour enhancement.

FEATURES

- ✓ UV resistant.
- ✓ Easily applied.
- ✓ Can be used for trafficable surfaces.
- ✓ Water resistant.
- ✓ Can be easily overcoated.
- ✓ Same day application over Westox Pavers.

TECHNICAL DATA

Specific Gravity	0.84 ± 0.03
Solids	approx. 21% V/V 24% W/W
Flash Point	35°C

PREPARATION

The surface to be treated should be clean and sound, free from oil, grease, flaking paint, laitance and materials deleterious to the adhesion of the coating system.

All surfaces shall be dry to allow for maximum adhesion.

- ✗ Do not apply if temperature is below 10°C or above 35°C.
- ✗ Do not apply if rain is imminent.

APPLICATION

Application by brush or lambswool roller.

Depending on substrate apply at 8 – 10m² per Litre per coat. Two coats required.

If applying before Paver Sealer, apply one coat and allow a minimum of 16 hours drying before applying a coat of Westox Paver Sealer at the rate of 5m² per Litre. (depending on the applied texture).

CLEAN UP

Wash equipment in xylene based thinners.

PACKAGING

4 Litre, 20 Litre

SHELF LIFE

12 months.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.

Material is flammable. Avoid contact with skin and inhalation use ventilation equipment.

DO NOT ALLOW NAKED FLAME NEAR OPEN CONTAINERS.