

PUTTY LIME

TDS66 Rev4 17/02/20

DESCRIPTION

Calcium Hydroxide – Putty Lime (General purpose and plastering Lime).

USES

Limes are the base of most traditional mortars and plaster mixes. Limes should be slaked for a minimum of 14 days prior to use when using in finishing materials. Slaked Limes are also used in our pre-mixed mortars.

TECHNICAL DATA

Putty Lime SG 1-1 to 1-3 60% by weight water, 40% by weight Lime

PREPARATION

To remove excess water from any of the Slaked Limes, pour the lime into a ring made in a sand pit and leave overnight.

MIXING

Lime mortars can be mixed by hand or by mechanical mixers.

APPLICATION

For specific uses and formulations containing Lime products consult our technical department.

PRECAUTIONS

All Limes are caustic. Care should be taken and the correct safety equipment should be worn when handling these materials.

PACKAGING

20 Litre & 200 Litre.

STORAGE

Storage life is indefinite provided the Lime is not allowed to dry out.

SHELF LIFE

3 years.

SAFETY

Refer to Westlegate Pty Ltd Safety Data Sheet (SDS) for instructions.



Westlegate Pty Ltd
16 Frost Road Campbelltown NSW 2560
Ph: 61 2 46285010 Fax: 61 2 46285020
Email: info@westox.com Website: www.westox.com