

MASON'S PUTTY

TDS105 Rev0 17/02/20

DESCRIPTION

Westox Mason's Putty is a traditional lime based putty formulated with linseed oil for stonework joints.

USES

Pointing and re-pointing mortar joints of sandstone, marble and other natural stones.

FEATURES

- ✓ Pre-mixed
- ✓ Colour – natural white
- ✓ Excellent working characteristics
- ✓ Consistency of product

APPLICATION

Surfaces to be pointed should be dry, free of dust, grease, loose materials or any other substances that may affect the adhesion of the Westox Mason's Putty. Apply the putty to the prepared stonework by hand placement using the appropriate tool, then trim off any excess and strike to the required finish.

COVERAGE

Coverage is approximately 200L/m per 20kg (10Litres) @ 5mm wide x 10mm deep.

DRYING TIME

Skin forms after 2 - 4 days dependent on ambient temperature and humidity.
Curing time depends on thickness of application and environmental conditions.

LIMITATIONS

Do not apply during inclement weather.
Do not apply in temperatures below 5°C or above 30°C.
Linseed oil may cause staining to some porous materials.

CLEAN UP

Wash all equipment with white spirits immediately after use.

PACKAGING

20kg containers.

SHELF LIFE

12 months in unopened containers stored in cool, dry conditions.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.