

RAP PRIMER

TDS12 Rev6 17/02/20

DESCRIPTION

A pure acrylic primer with high penetrating properties.

USES

Used for wood lath ceiling reinstatement, re-establishing the adhesion of drummy plaster and render by injection, as a consolidator of friable substrates and as a Primer for the Westox Lime Wash.

TECHNICAL DATA

Adhesion Excellent to all surfaces.

pH 8.5 ± 1

PREPARATION

Clean surface and remove all surface dirt, flaking paint etc.

Repair unsound substrate.

For Westox Ceiling Reinstatement (where accessible) remove all dust and loose debris from the back of the laths with an industrial vacuum cleaner being careful not to disturb the plaster keys. Do not thin out material.

APPLICATION

Ceiling Reinstatement

Apply a flood coat at 1m² per Litre with a mechanical or hand pump.

Primer

When used as a primer for lime wash, allow approximately 5m² per Litre.

Apply with brush or roller.

CLEAN UP

Wash all equipment in fresh water immediately after use.

PACKAGING

5 Litre & 20 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westlegate Pty Ltd Safety Data Sheet (SDS) for instructions.



Westlegate Pty Ltd
16 Frost Road Campbelltown NSW 2560
Ph: 61 2 4628 5010 or 1300 937 869
Email: info@westox.com Website: www.westox.com