

## CRETESEAL

TDS22 Rev6 17/02/20

### Concrete Floor Sealer

#### DESCRIPTION

CreteSeal is a one component penetrating acrylic sealer / binder.

#### USES

As a sealer / dustproofer for concrete and cementitious floors. Ideal for car parks, warehouses etc.

#### FEATURES

- ✓ Single component
- ✓ Excellent adhesion
- ✓ Resists Mild Chemicals
- ✓ Abrasion resistant

#### PREPARATION

The surface to be treated should be clean and sound, free from oil and grease or any existing coating or sealer, and materials deleterious to the adhesion of the Westox CreteSeal. New concrete should be a minimum of 28 days before application commences.

All repairs to the concrete should be made prior to the application of the coating.

Do not apply if temperature is below 10°C or above 35°C.

Do not apply if rain is imminent.

#### APPLICATION

For dustproofing and surface hardening of concrete. Apply two coats of CreteSeal at the rate of approximately 10m<sup>2</sup> per Litre. Allowing a four (4) hour drying time between coats. The coverage rate will vary on the porosity of the concrete. Product can be applied with either brush, roller or airless spray.

#### CLEAN UP

Wash all equipment with fresh water immediately after use and before material has dried.

#### PACKAGING

10 Litre & 20 Litre.

#### SHELF LIFE

12 months.

#### SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.