

## PAVER SEALER

TDS29 Rev6 17/02/20

### DESCRIPTION

A single pack, clear thermoplastic acrylic co-polymer solution for the coating of various masonry substrates.

### USES

As a sealer coat for concrete floors, driveways, exposed aggregate and slate floor tiles.

### FEATURES

- ✓ Easily applied
- ✓ Water resistant
- ✓ Can be easily overcoated
- ✓ UV Resistant (no yellowing)
- ✓ Can be used for trafficable surfaces

### TECHNICAL DATA

Specific Gravity	0.9
Volume Solids	approx. 25%
Flash Point	24°C
Chemical resistance	Good resistance to mild acids and alkalines.

### PREPARATION

The surface to be treated should be clean and sound, free from oil, grease, flaking paint, laitance and materials deleterious to the adhesion of the coating system.

New concrete should be a minimum of 28 days old before application commences.

All holes and cracks are to be repaired prior to coating.

Do not apply if temperature is below 10°C or above 35°C.

Do not apply if rain is imminent.

### APPLICATION

Application by brush, lambswool roller or airless spray. Applied in two coats at 8-10m<sup>2</sup> per Litre, per coat.

### CLEAN UP

Wash all equipment with Westox General Purpose Thinners immediately after use.

### PACKAGING

4 Litre & 20 Litre.

### SHELF LIFE

12 months.

### SAFETY

Refer to Westlegat Pty Ltd Safety Data Sheet (SDS) for instructions.



**Westlegat Pty Ltd**  
**16 Frost Road Campbelltown NSW 2560**  
**Ph: 61 2 4628 5010 Ph: 1300 WESTOX**  
**Email: [info@westox.com](mailto:info@westox.com) Website: [www.westox.com](http://www.westox.com)**