

SEALER BINDER

TDS71 Rev6 17/02/20

Concrete Floor Sealer and Consolidation Treatment

DESCRIPTION

Westox Sealer Binder contains a combination of liquid silica, silane and an acrylic resin.

USES

Sealer Binder can be used as a concrete floor sealer or as a calcium converter during remedial works on concrete surfaces previously affected by efflorescence, such as balconies and roof tops.

FEATURES

- ✓ Single component
- ✓ Excellent penetration qualities
- ✓ Chemical resistant
- ✓ Abrasion resistant
- ✓ High water resistance.

PREPARATION

The surface to be treated should be clean and sound, free from oil and grease or any existing coating or sealer, and materials deleterious to the adhesion of the Sealer Binder. New concrete should be a minimum of 28 days before application commences. All repairs to the concrete should be made prior to the application of the coating. Do not apply if temperature is below 10°C or above 35°C. Do not apply if rain is imminent.

APPLICATION

For sealer and calcium converter on concrete. Apply two coats of Sealer Binder at the rate of approximately 4 - 6m² per Litre. Allowing 4 hours drying time between coats. The coverage rate will vary on the porosity of the concrete. Product can be applied with brush, roller or airless spray.

CLEAN UP

Wash all equipment with fresh water immediately after use.

PACKAGING

20 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.