

WESFLEX

TDS07 Rev6 17/02/20

High Quality Surface Finish Coating

DESCRIPTION

Westox Wesflex is a water based, fast drying flexible coating for use on exterior applications. Westox Wesflex is a high quality surface finish coating, exhibiting excellent flexibility and durability.

USES

Westox Wesflex is designed to provide a durable exterior weatherproof finish. Westox Wesflex exhibits outstanding water resistance and crack spanning abilities and may be used for exterior work, where aesthetics and performance are of paramount importance.

FEATURES

- ✓ Water Resistant
- ✓ Can be recoated.
- ✓ Wide colour range
- ✓ Excellent resistance to cracking and chalking.
- ✓ High resin content.
- ✓ Excellent flexibility.
- ✓ Long life coating.
- ✓ Excellent resistance to fungus attack.

TECHNICAL DATA

- UV Stability Excellent
- Specific Gravity 1.2
- pH 8.5 – 9.0
- Solids 55± 1%
- Finish Satin
- Boiling Point 100°C water based.
- Not suitable for permanent immersion.
- Elongation – In excess of 200% @ 25°C un-reinforced.
- Chemical Resistance: Resists mild chemical environments and airborne pollutants.

PREPARATION

The surface to be treated should be clean and sound, free of oil, grease, flaking paint, laitance and material deleterious to the adhesion of the coating system.

Not recommended for below grade waterproofing.

New concrete should be a minimum of 28 days old before application commences.

All holes and cracks are to be repaired prior to coating.

Do not apply coating if temperature is below 10°C or above 35°C.

Do not apply coating if rain is imminent.

APPLICATION

Apply Wesflex at the coverage rate of 5 - 6m² per Litre per coat. Two coats required.

Apply with a 20mm nap roller.

Allow 4 hours drying time between coats. The two coats will give a minimum D.F.T of 180 microns.

CLEAN UP

Wash all equipment in fresh water immediately after use.

PACKAGING

15 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westlegate Pty Ltd Safety Data Sheet (SDS) for instructions.