

WESPRIME

TDS38 Rev6 17/02/20

DESCRIPTION

A cost effective resin rich primer based on a pure acrylic resin.

USES

Wesprime is a pre-mixed primer. It is an excellent primer for wood, cement roof tiles, cement render, concrete or previously coated sound substrates that are to be coated with Westox Colourcote, Satintex, Glosstex or Wesdex. Wesprime can also be used as a clear glaze coat over WX Colourcote.

PREPARATION

All surfaces to be coated must be clean, dry and free of any material that may affect the adhesion of the primer. Repair any unsound substrate prior to coating.

APPLICATION

No mixing required. Apply by brush, roller or spray. If unsure of adhesion, carry out a small test section prior to full application. Allow primer to dry for a minimum 1 hour @ 25°C before applying top coats. A longer cure time will be required in lower temperatures.

TECHNICAL DATA

Drying Time	Approximately 20 mins @ 25°C
Recoat Time	Approximately 1 hour @ 25°C
Solids as supplied	25% + - 3%
Coverage	5 - 6m ² per Litre, one coat.

CLEAN UP

Clean all equipment in water immediately after use.

PACKAGING

4 Litre & 20 Litre.

SHELF LIFE

12 months

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.

