

HIGH BUILD ACRYLIC FILLER COARSE

TDS85 Rev2 29/11/2021

DESCRIPTION

Westox High Build Acrylic Filler is a brilliant white render filler where outstanding performance of filling is desired on primed surfaces wherein high degree of smooth levelling and filling joints are needed on wall, masonry surfaces or even on plastic substrates.

USES

Used on primed surfaces viz; concrete, brick, parapet walls, flat and pitched roofs, liquid flashing, FC and AC sheeting, following spalling concrete repairs, silos, cement render, plant rooms and low traffic walkways.

TYPES

Coarse SG 1.6 – 1.8

PREPARATION

The High Build Acrylic Filler is to be applied onto a pre-primed surface of Westox High Block Primer and should be clean and free from oil, grease, flaking paint, laitance and other loosely adhered materials.

Ensure the High Block Primer (C or E Gel) is thoroughly dried before applying High Build Acrylic Filler.

APPLICATION

Apply by trowel to primed surface.

Vertical Surfaces

Apply Westox High Build Acrylic Filler Coarse by trowel one coat at the rate of 1m² per Litre for 1mm dry film thickness and allow to dry overnight. This will help large filling joints and major dents to level uniformly.

Horizontal Surfaces

Apply Westox High Build Acrylic Filler Coarse by trowel one coat at the rate of 1m² per Litre for 1mm dry film thickness and allow to dry overnight. This will help large filling joints and major dents to level uniformly.

Do not thin out material.

Do not apply HB Acrylic Filler if temperature is below 5°C or over 35°C.

Do not apply HB Acrylic filler if rain is imminent or in high humidity.

CLEAN UP

Wash all equipment in fresh water immediately after use.

PACKAGING

15 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westlegate Pty Ltd Safety Data Sheet (SDS) for instructions.



Westlegate Pty Ltd
16 Frost Road Campbelltown NSW 2560
Ph: 61 2 4628 5010 Fax: 61 2 4628 5020
Email: info@westox.com Website: www.westox.com