

SUPER PRIMER

TDS108 Rev1 07/04/21

DESCRIPTION

Westox Super Primer is designed to improve the adhesion of tile adhesives and Westox coatings on various smooth and non-porous substrates such as ceramic tiles, porcelain and PVC formwork. A single component, water-based primer that is easy to use and suitable for internal and external applications.

USES

Westox Super Primer can be used over existing tiled floors to provide adhesion for tile adhesives when re-tiling is required, and also on PVC formwork prior to using Westox cement based waterproofing and tanking products. Westox Super Primer is not suitable for permanently submerged conditions such as pools and holding tanks.

PREPARATION

All surfaces to be coated must be clean, dry and free of any material that may affect the adhesion of the primer. Repair any unsound substrate prior to coating.

APPLICATION

Apply one coat by brush or roller @ 6-10m² per litre. If unsure of adhesion, carryout a small test section prior to full application. Allow primer to dry for a minimum of 1 hour @ 25°C before applying top coats. A longer cure time will be required in lower temperatures. On extremely porous substrates dilute 1 part Westox Super Primer with 1 part water by volume.

TECHNICAL DATA

Drying time	Approximately 20 minutes @ 25°C.
Recoat time	Approximately 1 hour @ 25°C.
Coverage	6-10m ² per litre, one coat.

CLEAN UP

Wash all tools and equipment in fresh water immediately after use.

PACKAGING

4 Litre
15 Litre

SHELF LIFE

12 months, store in a dry, cool place out of sunlight.

SAFETY

Refer to Westlegate Pty Ltd Safety Data Sheet (SDS) for instructions.



Westlegate Pty Ltd
16 Frost Road Campbelltown NSW 2560
Ph: 61 2 4628 5010 Ph: 1300 WESTOX
Email: info@westox.com Website: www.westox.com