

## D-LAM 100

TDS40 Rev7 09/05/24

### Controlled Paint Removal System

#### DESCRIPTION

Westox D-Lam 100 concentrate is a solvent based gel formulated for the removal of paint.

#### USES

To remove paint and coatings from timber, plaster and masonry.

#### FEATURES

- ✓ Non caustic
- ✓ Can be used on most substrates
- ✓ Non methylene chloride

#### TECHNICAL DATA

S.G. 1.0 – 1.1  
Flashpoint (deg C) 52 (Pmcc)  
Miscible with water.

#### APPLICATION

Apply D-Lam 100 by roller or brush at the rate of approximately 2m<sup>2</sup> per Litre at 2mm thick.

The reaction time will depend on the type of paint and thickness of the applied layers.

It is advisable to apply a test area prior to the commencement of each project to assess its suitability and most effective application method.

#### CLEAN UP

Wash all equipment in fresh water immediately after use.

#### PACKAGING

4 Litre & 20 Litre.

#### SHELF LIFE

12 months.

#### SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.



**Westgate Pty Ltd**  
**16 Frost Road Campbelltown NSW 2560**  
**Ph: 61 2 46285010 or 1300 937 869**  
**Email: [info@westox.com](mailto:info@westox.com) Website: [www.westox.com](http://www.westox.com)**