

D-LAM 20

TDS39 Rev6 17/02/20

Controlled Paint Removal System

DESCRIPTION

Westox D-Lam 20 is a solvent-based paint removal system in an easy-to-use paper pulp carrier.

USES

Used to remove paint coatings from timber, plaster and masonry. By timing the application paint can be removed 1 coat at a time or several coats together. The D-Lam 20 is ideal for exposing heritage stencil work that has been hidden by numerous coats of paint and for graffiti removal.

FEATURES

- ✓ Non caustic
- ✓ Controllable
- ✓ Can be used on most substrates
- ✓ Non methylene chloride
- ✓ Self Neutralising
- ✓ Easy to use

TECHNICAL DATA

S.G.	1.02 – 1.04	Flashpoint (deg C)	62 (Pmcc)
Miscible with water			

PREPERATION

It is advisable to apply a test area prior to the commencement of each project to assess its suitability and to determine the most effective application method.

APPLICATION

Apply D-Lam 20 by trowel at approximately 3 to 4mm thickness. Reaction time can be as short as 20 minutes for one coat removal and 24 hours to remove up to six coats.

After the required dwell time, remove the D-Lam 20 from the surface and avoid removing the coating, place the D-Lam 20 into a bucket and mix 50/50 with fresh D-Lam 20 ready to use again. Remove the softened paint separately and dispose of in the appropriate manner. Re-apply the remixed D-Lam 20 and repeat procedure until the desired removal is completed.

CLEAN UP

Wash all equipment in fresh water immediately after use.

PACKAGING

4 Litre & 20 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westlegat Pty Ltd Safety Data Sheet (SDS) for instructions.

