

GLOSSTEX

TDS04 Rev7 17/02/20

High Build Gloss Profiled Coating

DESCRIPTION

A high gloss finish with a low dirt retention, maximum protection and exceptional longevity.

USES

An aesthetically pleasing architectural texture finish coating for exterior use.

FEATURES

- ✓ Wide colour range
- ✓ Water based, premixed
- ✓ UV stable, high gloss texture finish
- ✓ Does not chalk
- ✓ Outstanding flexibility
- ✓ Exceptionally durable
- ✓ Low dirt retention
- ✓ Exterior use

TECHNICAL DATA

Volume Solids	53% ± 0.5%
Specific Gravity	1.15 ± 0.05
Elongation to break	350% @ 20°C
Adhesion to substrate	25.4Kgf / cm ²

PREPARATION

The surface to be treated should be clean and sound, free of oil, grease, flaking paint, laitance and material deleterious to the adhesion of the coating system.

Not recommended for below grade waterproofing.

New concrete should be a minimum of 28 days old before application commences.

All holes and cracks are to be repaired prior to coating.

Do not apply coating if temperature is below 10°C or above 35°C.

Do not apply coating if rain is imminent. Sound paint may be over coated.

APPLICATION

Apply Westox Glosstex by brush, texture roller or spray to the prepared pre-primed surface at the rate of 1 - 1.5m² per Litre.

CLEAN UP

Wash all equipment in fresh water immediately after use.

PACKAGING

15 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.

