

# NON WHITENING CONCRETE SEALER

---

TDS69 Rev6 17/02/20

## Concrete Floor Sealer and Consolidation Treatment

### DESCRIPTION

Non Whitening Concrete Sealer contains a combination of liquid silica, silane and an acrylic resin.

### USES

As a sealer / dustproofer for concrete and cementitious floors. Ideal for driveways, carparks and warehouses.

### FEATURES

- ✓ Single component
- ✓ Excellent penetration qualities
- ✓ High water resistance.
- ✓ Chemical resistant
- ✓ Abrasion resistant

### PREPARATION

The surface to be treated should be clean and sound, free from oil, grease or any existing coating or sealer, and materials deleterious to the adhesion of the Non Whitening Concrete Sealer. New concrete should be a minimum of 28 days before application commences.

All repairs to the concrete should be made prior to the application of the coating.

Do not apply if temperature is below 10°C or above 35°C.

Do not apply if rain is imminent.

### APPLICATION

For sealing and coating of concrete and masonry floors. Apply two coats of Non Whitening Concrete Sealer at the rate of approximately 8 - 10m<sup>2</sup> per Litre per coat. Allowing 4 hours drying time between coats. The coverage rate will vary on the porosity of the concrete. Non Whitening Concrete Sealer can be applied with either brush, roller or airless spray.

### CLEAN UP

Wash all equipment with fresh water immediately after use.

### PACKAGING

20 Litre.

### SHELF LIFE

12 months.

### SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.

