

PLASTALITE TUCKPOINT

TDS19 Rev8 12/3/25

DESCRIPTION

Tuckpoint is a fine sand, lime and Pozzuolanic material with a small amount of cement designed to provide a mortar mix with a moderate strength which will not be detrimental to the brick or stone where it is used.

USES

A ready formulated product for traditional tuckpointing. The material can also be used for pointing sandstone where the appearance of mason's putty is required.

FEATURES

- ✓ Available in White, Off White, Buff & Black
- ✓ Gunable
- ✓ Easy to use
- ✓ Consistent quality
- ✓ Compatible with other mortars
- ✓ Sacrificial in a salt environment
- ✓ Minimum shrinkage after tooling
- ✓ Non staining of stone

TECHNICAL DATA

Setting time	30 to 45 minutes for initial set
S.G.	1.25
Compressive Strength	7 - 8 MPA

COVERAGE

Tuckpointing - 5mm x 2mm	20kg = approximately 1000L/m.
Repointing stone - 5mm x 20mm	20kg = approximately 130L/m.

APPLICATION

Brick - Apply with brick key for traditional tuckpointing.

Stone - Use Tuckpoint to simulate mason's putty. For narrow stone joints rake out to a minimum of 20mm deep and apply with pointing gun or trowel to previously dampened surface.

New pointing should be kept **damp for a minimum of 4 days** to ensure full cure if used without the mortar modifier.

MIXING

Add Mortar Modifier to the Tuckpoint powder and mix to a useable consistency.

PACKAGING

20kg bag Tuckpoint / Mortar Modifier 5Lt

SHELF LIFE

6 months in unopened bag.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.

