

## SATINTEX

TDS05 Rev7 17/02/20

### High Performance Architectural Profile

#### DESCRIPTION

A natural grain appearance provides soft to medium profiles, enhancing building design characteristics to suit the most fastidious of owners.

#### USES

For weatherproofing, decorating, restoring and protecting exterior walls and to enhance existing building environments.

#### FEATURES

- ✓ Easily applied
- ✓ Wide colour range.
- ✓ Can be overcoated to provide satin or gloss finish.
- ✓ Weather and UV resistant.
- ✓ Extremely durable.
- ✓ Water based, premixed.

#### TECHNICAL DATA

Volume Solids	68% $\pm$ 1%
Specific Gravity	1.4
Flexibility	60% @ 20°C
Finish	Satin or Gloss

#### PREPARATION

The surface to be treated should be clean and sound, free of oil, grease, flaking paint, laitance and material deleterious to the adhesion of the coating system.

New concrete should be a minimum of 28 days old before application commences.

All holes and cracks can be repaired prior to coating.

Do not apply coating if temperature is below 10°C or above 35°C.

Do not apply coating if rain is imminent. Sound coatings may be overcoated.

#### APPLICATION

Application by brush, texture roller or spray to the prepared pre-primed surface.

Apply at the rate of 1 - 1.5m<sup>2</sup> per Litre and finish to the required texture.

Do not thin material.

#### CLEAN UP

Wash all equipment with fresh water immediately after use.

#### PACKAGING

15 Litre.

#### SHELF LIFE

12 months.

#### SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.



Westgate Pty Ltd  
16 Frost Road Campbelltown NSW 2560  
Ph: 61 2 4628 5010 or 1300 937 869

Email: [info@westox.com](mailto:info@westox.com) Website: [www.westox.com](http://www.westox.com)