

WX COLOURCOTE

TDS07 Rev6 17/02/20

Resin Rich Acrylic Coating

DESCRIPTION

A resin rich, low viscosity, high solids co-polymer colour coating for a variety of surfaces.

USES

Used as a coating for the refurbishment of concrete roof tiles, wood and various concrete surfaces where a gloss coating is required.

FEATURES

- ✓ Extremely durable, water based.
- ✓ Easily applied & easily over coated.
- ✓ UV resistant protective coating.
- ✓ Wide colour range.
- ✓ Excellent gloss retention.
- ✓ Aesthetically pleasing finish.

TECHNICAL DATA

Volume Solids	50% +/- 1
Specific Gravity	1.13 +/- 0.05
Elongation to break	100%
Finish	Gloss
Chemical resistance	Resists mild chemical environment.

PREPARATION

The surface to be treated should be clean and sound, free of oil, grease, flaking paint, laitance and material deleterious to the adhesion of the coating system.

Not recommended for below grade waterproofing.

New concrete should be a minimum of 28 days old before application commences.

All holes and cracks are to be repaired prior to coating.

Do not apply coating if temperature is below 10°C or above 35°C.

Do not apply coating if rain is imminent. Sound paint may be over coated.

APPLICATION

Application by brush, roller or spray to prepared, pre-primed surfaces at the rate of 6 - 8m² per Litre. Touch dry in approximately 15 minutes. If appropriate apply second coat at 6 - 8m² per Litre allowing a minimum four (4) hour drying period between coats.

CLEAN UP

Wash all equipment in fresh water immediately after use.

PACKAGING

15 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.



Westgate Pty Ltd
16 Frost Road Campbelltown NSW 2560
Ph: 61 2 4628 5010 or 1300 937 869

Email: info@westox.com Website: www.westox.com