

HANDY MORTAR

TDS60 Rev7 17/02/20

DESCRIPTION

Handy Mortar is a sand, lime and cement (6:1:1) based fine mortar formulated to be used on a wide range of substrates.

USES

For applying a bagged finish on feature walls etc or as a material for blow holes in concrete. As a general repair material for render finishes, can be used for repointing or laying bricks or stone.

FEATURES

- ✓ Fast mixing
- ✓ Assured mix ratios
- ✓ Reduced Labour cost
- ✓ Consistent adhesion to most substrates
- ✓ Can be feathered at joins
- ✓ Easy to use
- ✓ Can be trowel pressed or sponge finished
- ✓ Ideal for making good render prior to painting

PREPARATION

All surfaces must be free of efflorescence, dust, dirt, oil, paint or other substances which may inhibit adhesion of the mortar.

Salt analysis and desalination may be required to increase the longevity of the mortar and the protection of the building material. Refer to Westox Technical Department for more information on the Westox Cocoon Desalination System.

Acid cleaned surfaces should be washed down with a neutralising agent prior to application.

Water blasted surfaces should be allowed to dry for a minimum of 24 hours before repairing.

Surfaces should be dampened before application.

Do not apply during inclement weather

Do not apply in temperatures below 5°C or exceeding 30°C.

MIXING

Each 20kg bag of handy mortar will require approximately 4 - 5 Litres of water to reach a workable consistency. For a high profile a stiffer mix containing less water may be required.

CLEAN UP

Wash all equipment with fresh water immediately after use.

PACKAGING

20kg bag.

SHELF LIFE

6 months.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for Instructions.