

PLASTALITE MULTI FINISH

TDS32 Rev7 17/02/20

DESCRIPTION

Plastalite Multi Finish is a skim coat for interior use over render or plasterboard which provides a hard, flat, smooth surface ready for painting.

USES

Used as a finish coat for Plastalite Bonding, Browning and Metal Lathing Plaster. Plastalite Multi Finish can also be used over Plastalite Rehabilitation Render or traditional sand and lime renders for interior work. Multi Finish is compatible with heritage and modern plasters.

FEATURES

- ✓ Easy to mix.
- ✓ Easy to use.
- ✓ Can be feathered and polished.
- ✓ Just add to water.
- ✓ Extended set time with slower hardening.

TECHNICAL DATA

Application Thickness	2 - 3 mm
Set Time	45 minutes - 60 minutes
Approximate coverage per 20kg bag	10 - 12m ²

APPLICATION

Mix by adding Plastalite Multi Finish to water in a suitable mixing vessel, mix to usable consistency. Apply with a steel trowel at approximately 2 - 3mm thick to entire area. After initial set, mix fresh material and "Lay Down" another coat to fill any holes or voids in the first coat, complete by troweling water over the surface until a satisfactory acceptable finish is obtained. Minimum time before painting three (3) weeks.

LIMITATIONS

Plastalite Multi Finish cannot be used for external applications or internal wet areas (bathrooms) for exterior or wet area applications refer to Plastalite Rehabilitation Render or Plastalite Fairing Coat Data Sheets.

CLEAN UP

Wash all equipment in fresh water immediately after use.

PACKAGING

20kg bag.

SHELF LIFE

3 months.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.

