

WESDEX

TDS09 Rev7 09/05/24

Flexible Deck Coating

DESCRIPTION

A granular profile coating formulated to provide a flexible finish for pedestrian traffic areas.

USES

For weatherproofing, decorating, restoring and protecting, walkways, patios and decks.

FEATURES

- ✓ Wide colour range
- ✓ Easily applied
- ✓ Extremely durable
- ✓ Water based, no mixing required
- ✓ Weather and UV resistant
- ✓ Walkways, patios & decks

TECHNICAL DATA

Specific Gravity at	1.4
Volume Solids	68% $\pm$ 1%
Flexibility	60% @ 20°C
Finish	Satin

PREPARATION

The surface to be coated should be clean and sound, free from oil, grease, flaking paint, laitance and other deleterious materials.

Not recommended for below grade waterproofing or concrete subject to rising or hydrostatic moisture.

New concrete should be a minimum 28 days old before application commences.

All holes and cracks should be repaired prior to coating.

Do not apply if temperature is below 10°C or above 35°C.

Do not apply coating externally if rain is imminent.

APPLICATION

Apply the appropriate Westox Primer.

Apply Westox Wesdex by brush, texture roller or spray to the prepared pre-primed surface.

Apply at the rate of 1 - 1.5m² per Litre and finish off immediately to the required finish.

May also be spray applied using Westox Spray Unit or similar equipment.

Drying time depends on weather conditions.

Do not thin material.

Do not apply coatings if surface temperature is below 10°C or in declining temperatures (ambient temperature is below 15°C or over 35°C).

Do not apply coating if rain is imminent.

Will achieve full cure in 7 days.

Avoid water ponding for first 3 days minimum after application.

CLEAN UP

Wash all equipment with fresh water immediately after use.

PACKAGING

15 Litre.

SHELF LIFE

12 months.

SAFETY

Refer to Westlegate Pty Ltd Safety Data Sheet (SDS) for instructions.